

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

adds TROTON SPRAY WHITE LUBRICANT



PRODUCT DESCRIPTION

High quality lubricant spray to lubricate mechanical parts made of metal or plastic. Prevents against mechanical damages and creaking, provides excellent adhesion and mechanical and thermal stability. Resistant to the weather conditions and the action of weak acids and bases. Product has excellent anti-corrosion performance, water-repellent. Contains polytetrafluorethen (PTFE).

PHYSICAL AND CHEMICAL PROPERTIES

Color:	white
Volume:	400 ml.
Glass grade:	mat
Density:	0,67 g/ml (20 ⁰ C)
Yeld:	1,5 g/sec
Temperature resistance:	from -30 to +160 ⁰ C

CONTENT OF VOLATILE MATTER

VOC = 498 [g/l]

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.

USAGE

- Best work temperature is 5 – 30°C.
- Shake can before use for 2 minutes and try it on cardboard.
- Apply white lubricant in a thin layer.
- The best lubrication is received after evaporation of the solvent.
- **After use clean aerosol's outlets** – hold down aerosol's valve, push the bottom and release contents for 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date, provided the storage condition.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland