

Technical information

October 2007

**THE PRODUCT IS SUITABLE FOR
PROFESSIONAL USE ONLY**

INTER TROTON SPRAY PLASTIC PRIMER

PRODUCT DESCRIPTION

Quick-drying, top quality filler for convert and an convert surface. It's good adhesion ability acryl and polyurethane product to plastic. Easy to use and very productive.

PHYSICAL AND CHEMICAL PROPERTIES

Colour:	colorless
Glass grade:	matt
Capacity:	2 ÷ 3 m ²
Volume:	400ml
Ready to use:	after 10-15 min

VOLATILE COMPONENTS CONTENT

VOC =693 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

SUBSTRATE AND SURFACE PREPARATION

Recommended to all type of plastics surface.

Caution: Filler do not improve adhesion in polyethylene surface, PE.

Surface should be degreased, dulled with the abrasive cloth and degreased again with detergent, water rinse and air dry.

It is recommended to warm element in temperature 50°C for better remove silicone product of the surface

GENERAL NOTES

Best use temperature 15÷25 °C

Shake before using for 2 minutes and try it on cardboard.

During lacquering hold aerosol in 25÷30 cm distance for metal surface.

Apply lacquer in few thin layers, in time intervals not longer than 5 – 10 minutes. Before applying of next layer shake the container again.

After use clean aerosol's outlets – hold down aerosol's valve, push the bottom and release contents for 5 min.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

WARRANTY PERIOD

Inter Troton Spray Plastic Primer -12 months from the production date

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practices.

TROTON sp. z o.o. Ząbrowo