

Mipa 2K-Klarlack CA

gb 5/0811

page 1 / 1

Professional Coating Systems

Product Information

2K-MS Clear coat based on high quality acryl resins with UV-protection and direct adhesion to blank ferrous and non-ferrous metals. The application of Mipa 2K-Klarlack CA will have no influence on the original appearance of the substrate. Consumption: $6 - 8 m^2 / I$.

Colour shade	transparent					
Mixing ratio	5 : 1 by volume					
Hardener	Mipa 2K - Härter MS 10, MS 25 or MS 40					
Thinners	Mipa 2K - Verdünnung; add about 10%					
Spraying viscosity 20°C	18 - 20 s 4 mm DIN					
Application	spraying pressure		sprayii	ng nozzle	spraying operation	ns
Air / Flowjar – Spray gun	2 - 3 bar		1.4 mm		2	
Airless / Airmix						
Pot life	6 - 8 h					
Coat thickness / dry film	40 - 50 μm					
Curing time / Flash off time	5 - 10 min. between the spraying operations					
Dry	recoat time	du	st dry	set to touc	h full hardness	\$
Object temp. 20°C		20 - 30 min.		6 - 8 h	24 h	
Object temp. 60°C	5 - 10 min.		30 - 40 m	nin. 1 - 2 h		
VOC content	EU limiting value for the product (cat. B/e): 840 g/l This product contains max. 550 g/l VOC [4.59 lbs/gal]					

Operation conditions: from + 10 $^{\circ}$ C and up to 75% relative air humidity. **Recommandation:**

The reddish shade of this product will disappear after application.

Mipa 2K-Klarlack CA may be coloured with Mipa Brillant-Design or Mipa 2K-PUR-Autolack OC (addition max. 20%).

Mipa 2K-Klarlack CA is not suitable for application as clearcoat on polished metals. More than that, before starting the application on special metal supports (such as very smooth and hard Eloxal coat), all necessary precautions should be taken to assure the direct adhesion to the substrate.

Storage: at least 3 years in tightly closed original containers.

This data sheet is for information purpose only! To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty. Please follow recommendations stated on the relevant safety data sheet and precautions stated on the product label. We reserve our right to make additions, deletions, or modifications to the information at any time without prior notification.