

Printing date 06/10/2014 Reviewed on 06/10/2014

1 Identification

- · Product identifier
- · Trade name: HR014 Hot Rod Black
- · Article number: HR014
- $\cdot \textit{Relevant identified uses of the substance or mixture and uses advised against}$

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

(Contd. on page 2)

Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 1)

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous o	components:	
	ACRYLIC RESIN	13 - 30%
67-64-1	acetone	13 - 30%
123-86-4	n-butyl acetate	13 - 30%
9004-36-8	CELLULOSE ACETATE BUTYRATE	5 - 7%
	precipitated Silica (Silica-Amorphous)	
110-43-0	heptan-2-one	5 - 7%
108-83-8	2,6-dimethylheptan-4-one	1.5 - 5%
1330-20-7	xylene	1.5 - 5%
14807-96-6	Talc	1.5 - 5%
19549-80-5	4,6-dimethylheptan-2-one	1.5 - 5%
1333-86-4	Carbon black	1-1.5%

(Contd. on page 3)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

	(Co	ntd. of page 2)
41556-2	-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate	≤1%
82919-3	-7 Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate	≤1%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

	Tot parameters		
	· Components with limit values that require monitoring at the workplace:		
	67-64-1 acetone		
PEL	Long-term value: 2400 mg/m³, 1000 ppm		
REL	Long-term value: 590 mg/m³, 250 ppm		
TLV	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm		
	Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm		
	BEI		
	86-4 n-butyl acetate		
	Long-term value: 710 mg/m³, 150 ppm		
REL	Short-term value: 950 mg/m³, 200 ppm		
	Long-term value: 710 mg/m³, 150 ppm		
TLV	Short-term value: 950 mg/m³, 200 ppm		
	Long-term value: 713 mg/m³, 150 ppm		
-	precipitated Silica (Silica-Amorphous)		
PEL	20mppcf or 80mg/m3 /%SiO2		
REL	Long-term value: 6 mg/m³		
	See Pocket Guide App. C		
	TLV withdrawn		
110-4	110-43-0 heptan-2-one		
PEL	Long-term value: 465 mg/m³, 100 ppm		
REL	Long-term value: 465 mg/m³, 100 ppm		
TLV	Long-term value: 233 mg/m³, 50 ppm		
108-	108-83-8 2,6-dimethylheptan-4-one		
PEL	Long-term value: 290 mg/m³, 50 ppm		
REL	Long-term value: 150 mg/m³, 25 ppm		
	Long-term value: 145 mg/m³, 25 ppm		
1330	-20-7 xylene		
PEL	Long-term value: 435 mg/m³, 100 ppm		
	/G - 1 - 5		

(Contd. on page 5)

SEM

Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 4) REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm 1333-86-4 Carbon black PEL Long-term value: 3.5 mg/m³ REL | Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C TLV Long-term value: 3* mg/m³ *inhalable fraction · Ingredients with biological limit values: 67-64-1 acetone BEI 50 mg/L Medium: urine *Time: end of shift* Parameter: Acetone (nonspecific) 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	rties
Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
Flash point:	-18 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	0.97 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

 Solvent content:
 (Contd. of page 6)

 Organic solvents:
 54.5 %

 VOC content:
 27.9 %

 405.6 g/l / 3.38 lb/gl

 Solids content:
 45.5 %

 • Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3	
14807-96-6	Talc	2B	
1333-86-4	Carbon black	2B	
9002-88-4	POLYETHYLENE	3	
100-41-4	ethylbenzene	2B	

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 7)

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

1 4 7	T Company				
141	rans	nort	into	rmatior	1
					•

W 7 3 7	37 7	
1/N-	Number	

· DOT, ADR, IMDG, IATA

UN1263

· UN proper shipping name

 $\cdot DOT$

Paint

· ADR · IMDG, IATA 1263 Paint, special provision 640D

PAINT

- · Transport hazard class(es)
- $\cdot DOT$



· Class

3 Flammable liquids.

· Label

3

· ADR, IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, ADR, IMDG, IATA

II

(Contd. on page 9)

SEM

Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

		(Contd. of page 8)
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user · EMS Number:	Warning: Flammable liquids F-E, <u>S-E</u>	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		
· DOT · Remarks	ORM-D 49CFR 173.150,156,306	
· UN ''Model Regulation'':	UN1263, Paint, special provision 640D, 3, II	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Section 355	(extremely hazardous substances):
None of the i	ngredient is listed.
Section 313	(Specific toxic chemical listings):
	ACRYLIC RESIN
1330-20-7	xylene
14807-96-6	Talc
100-41-4	ethylbenzene
TSCA (Toxio	Substances Control Act):
67-64-1	acetone
123-86-4	n-butyl acetate
9004-36-8	CELLULOSE ACETATE BUTYRATE
110-43-0	heptan-2-one
108-83-8	2,6-dimethylheptan-4-one
1330-20-7	xylene
14807-96-6	Talc
19549-80-5	4,6-dimethylheptan-2-one
1333-86-4	Carbon black
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
9002-88-4	POLYETHYLENE
104810-48-2	alpha-3-(3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega hydroxypoly (oxy-ethylen)
104810-47-1	alpha-3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl)-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen)
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
25322-68-3	Polyethylene glycol

(Contd. on page 10)

acc. to OSHA HCS

Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 9)

· Proposition 65

· Chemicals known to cause cancer:		
1330-20-7	xylene	
1333-86-4	Carbon black	
100-41-4	ethylbenzene	
· Chemicals known to cause reproductive toxicity for females:		

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
67-64-1	acetone	Ι
1330-20-7	xylene	Ι
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)		
67-64-1		A4
1330-20-7		A4
14807-96-6	Talc	A4
	Carbon black	A4
100-41-4	ethylbenzene	<i>A3</i>

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

(Contd. on page 11)



Printing date 06/10/2014 Reviewed on 06/10/2014

Trade name: HR014 Hot Rod Black

(Contd. of page 10)

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver
- · Date of preparation / last revision 06/10/2014 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

 ${\it Skin Irrit.~2: Skin corrosion/irritation, Hazard~Category~2}$

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

 $STOT\ SE\ 3:\ Specific\ target\ organ\ toxicity\ -\ Single\ exposure,\ Hazard\ Category\ 3$

USA