

Technical information

May 2008

**THE PRODUCT IS SUITABLE FOR
PROFESSIONAL USE ONLY**

INTER TROTON CAVITY WAX

PRODUCT DESCRIPTION

Product, designed for protecting of closed profiles of car body from corrosion, using spray gun. It has good properties in penetrating gaps and moisture removing. It creates elastic, tight coating, protecting from water and salt influence. Unary product, based upon wax and impregnation products.

It does not react with lacquer coatings.

PHYSICAL AND CHEMICAL PROPERTIES

Colour:	amber
Volume:	1l
Viscosity:	20 – 25 s
Density:	0,85 – 0,89 kg/l
Temperature resistance:	-25 do 80°C
Yield for 1l:	ok. 0,1 kg/m ² in 100 µm wet layers
In touch dry:	90 - 120 minutes in 100 µm wet layers
Fully dry:	10 – 12 hours in 100 µm wet layers

VOLATILE COMPONENTS CONTENT

VOC = 401,6 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

SUBSTRATE AND SURFACE PREPARATION

- Covered surface must be clean, dry, dedusted, degreased and derusted.
- Shake container before use.
- Intergum should be applied with air gun under pressure of 3-6 bar.
- Optimum spraying distance is approximately 30 cm.
- To achieve thinner coatings wait, until previously applied layers become dry.
- Apply with air gun under pressure of 3-6 bar.

- Clean dirty surfaces and equipment with solvents.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight. Suggest store temperature 10 to 30 °C.

WARRANTY PERIOD

Inter Troton MI- agent to protection closed section -24 months from the production date

All the information is given to the best of our up-to-date knowledge. We take, however, no responsibility for results due to improper usage of our products or unskilful work.

Troton sp.z o.o. Zabrowo