

## TECHNICAL INFORMATION

FOR PROFESSIONAL UDE ONLY

### MASTER SPRAY PRIMER 1K



#### PRODUCT DESCRIPTION

Quick-drying primer suitable for wood, aluminium, metal, plastic, glass and stone. Easy to sand wet and dry. Product has anticorrosive properties, is characterized by very good coverage and can be overpainted with all lacquering systems ( 1k and 2k acrylic lacquers, alkyd resin, nitro cellulose).

#### PCHYSICAL AND CHEMICAL PROPERTIES

- Colour: grey, black, red
- Glass grade: mat
- Capacity: 500 ml.
- Efficiency: 1,5 – 2 m<sup>2</sup>
- Density: 0,767 g/cm<sup>3</sup> (in temp. 20<sup>0</sup>C)
- Temperature resistant: to 110<sup>0</sup>C

#### Drying time (in temp. 20<sup>0</sup>C) :

- Dust dry: after approx. 5 – 10 minutes
- Tack free: after approx. 10 - 20 minutes
- Completely dry: after approx. 2 hours

**Note:** Drying time depends on air temperature, humidity and thickness of the layer.

**VOLATILE COMPONENTS CONTENT**

VOC = 686,4 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

**USAGE**

- The best results are achieved applying at room temperature. The ambient temperature and the temperature of the product should be the same.
- Surface should be dry, degreased, clean from dirt and rust and gently sanded.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- Apply in several thin layers. Shake aerosol again before applying each layer.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

**STORAGE**

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

**WARRANTY PERIOD**

5 years from production date.