

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY acryl BLACK MAT, SEMIGLOSS, GLOSS



PRODUCT DESCRIPTION

Acrylic paint with high covering power on surfaces made of metal, wood, aluminium, glass and plastic. Product designed for the general use on internal and external parts of car body. The paint is not fading, is resistant for UV radiation, petrol, chemicals and weather conditions.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: black
- Glass grade: mat, semigloss, gloss
- Capacity: 500 ml.
- Efficiency: 1,5 – 2 m²
- Base: acrylic resin
- Density: 0,775 g/cm³ (in temp. 20⁰C)
- Temperature resistance: to 110⁰C

Drying time (in temp. 20⁰C)*:

- Dust dry: after approx. 5 – 10 minutes
- Tack free: after approx. 10 - 20 minutes
- Completely dry: after approx. 2 hours

*Drying time depends on air temperature, humidity and thickness of the layer.

VOLATILE COMPONENTS CONTENT

VOC = 714,3 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- The best results are achieved applying at room temperature. The ambient temperature and the temperature of the product should be the same.
- Surface should be dry, degreased, clean from dirt and rust and gently sanded.
- Apply a layer of primer suitable for the surface.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- Apply one or two layers, depending on the needs.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

EXPIRY DATE

5 years from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland

TROTON Sp. z.o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94

Tel/Fax: +48 94 35 126 22 Website: www.troton.com.pl Email: troton@troton.com.pl