

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON RUST FILLER



PRODUCT DESCRIPTION

RUST FILLER is a water – based primer and rust converter in one. It stops and neutralizes the corrosion process. Formed the primer coat with adhesion for following treatment with putty and clear coat. The product is characterized by quick drying time, very good solvent – resistance and is easy to apply. Recommended to use in automotive, industry, metal processing etc. Can be mixed with water.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: beige
- Smell: slight
- Density*: approx. 1.02 g/cm³
- Viscosity*: 10 – 16 sec (Ford Cup no.4)
- Capacity: 100 ml., 250 ml.
- pH value*: 1.50
- Efficiency for 100 ml: 2m²
- Drying time*: 6 – 8 h.

*at temp. 20⁰C and relative humidity of 50%

VOC - CONTANT

Product does not contain VOC.

USAGE

- Remove rust, fat, dirt and paint flakes which are infiltrated by corrosion. Use brush if it is necessary.
- Shake well bottle before use.
- Apply product evenly on the rusty surface.
- Depending on degree of corrosion is recommended to apply 3 – 4 layers.
- Wait until the end of reaction – surface change color for dark blue.
- Protected and dry area cover with primer or lacquer.

Warning: Use only in well ventilated area or outdoors.

Caution: To maintain safety, always follow the instructions given in the MSDS for the product.

STORAGE

Store in temp. 10 – 25⁰ and relative air humidity 60%
Protect from freeze and direct sunlight.

EXPIRY DATE

5 years from production date in the original packaging.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland