

## TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

# *adds*TROTON 1K ANTICORROSIVE EPOXY PRIMER SPRAY

### PRODUCT DESCRIPTION

1K primer designed for preparing the surface for the top coating. Product has excellent anticorrosion properties and guarantees very good insulation from moisture. Is perfect for spot repairs, may be covered by water-based or solvent-based systems. Can be applied directly on steel, galvanized steel, stainless steel, aluminium and old paint coatings, also can be applied wet-on-wet.

### PHYSICAL AND CHEMICAL PROPERTIES

- Base : epoxy resin
- Capacity : 400 ml.
- Colour: grey
- Density: 0,802 g/cm<sup>3</sup> / 20<sup>0</sup>C
- Curing time: 10 – 15 min / 20<sup>0</sup>C

### CONTENT OF VOLATILE MATTER

VOC = 679,1 [g/l]

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.

**USAGE**

- Surface should be dry sanded, degreased, cleaned and dry.
- Before using shake aerosol can for 2 minutes and try it on cardboard.
- Apply 2-3 layers of the primer for the prepared surface
- **After use clean aerosol's outlets** – hold down aerosol's valve, push the bottom and release contents for 5 seconds.

**Caution:** For safety reasons always comply with information provided in the Material Safety Data Sheet

**STORAGE**

Store the product components in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

**WARRANTY PERIOD**

5 years from the production date.