

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY PRIMER PREMIUM anticorrosive primer filler



PRODUCT DESCRIPTION

New generation acrylic primer with anticorrosive and filling properties. Product is characterized by good adhesion on metal and plastic. Fast drying and easy to sand. Can be coated with most of conventional car paints, including waterbased lacquers. Aerosol fan nozzle is used for optimal spraying.

CHEMICAL AND PHYSICAL PROPERTIES

Color:	light grey (RAL 7040) dark grey (RAL 7011)
Capacity:	500 ml.
Density:	0,824 g/cm ³ (temp. 20 ⁰ C)
Base:	acrylic resin

Sanding:

Depending on layer thickness, temperature and ventilation can be sanded by hand after 15 minutes (P320 – P600)

VOLATILE COMPONENTS CONTENT

VOC = 686,4 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- Surface to be treated must be carefully cleaned from rust, dirt, dust and old paint.
- Shake for 2 minutes before using and try it on carboard.
- During lacquering hold aerosol in 20 cm distance from surface.
- Best processing temperature is between 15⁰C and 25⁰C.
- Apply in several layers (max. 6 in 15 minute intervals) depending on the needs as priming or filling (is recommended to apply several thinner layers then one thick coating).
- Dry thoroughly each layer until has turned completely dry.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland